

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Polishers

PE 14-3 125

Order no. 406.813

Technical attributes	PE 14-3 125
Max. polishing pad diameter	160 mm
Max. back-up pad diameter	125 mm
No load speed	1100-3700 rpm
Power input	1400 watt
Power output	880 watt
Tool fixture	M 14
Size (L x H)	370 x 110 mm
Weight	2,2 kg

Ergonomic polisher with speed control trigger

- VR microprocessor control: with tachogenerator constant speed control, soft start, continuous speed control trigger, restart protection after power failure, overload protection, temperature monitoring and speed selection
- Accelerator switch for a slow and gentle start
- With its wide speed range it is perfect for working with polishing pads from Ø 80 mm upto max Ø 160 mm
- Recommended polishing pad Ø 140 mm
- High-powered motor: can handle extreme loads
- Ergonomic design
- Slim shaft handle and ergonomic grip cover to optimise handling and reduce fatigue when polishing
- 4 metres PUR H05-BQF cable: wear-resistant, flexible and highly resistant to cuts and abrasions
- Spindle lock

Standard equipment
1 side handle