

**FLEX-Elektrowerkzeuge GmbH**

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

**FLEX**

## Metal surface finishing

### LRP 1503 VRA

Order no. 324.442

**Boa pipe belt sander**

- Highly efficient and resilient motor for more power output
- VR full-wave electronic control: tachogenerator constant speed control, soft start, overload protection and speed selection
- Sanding belt replacement: quick and tool-free
- High-quality, spring-mounted sanding arm: light alloy with 2 deflection rollers. For optimum wrap-round on pipes, up to max. 270°
- Additional side handle: can be rotated 180°, for narrow places
- Swinging the supplementary grip locks the sanding arm to allow work in confined spaces, e.g. sanding hand rails near walls.
- This machine is also available in 110 V

Technical attributes	LRP 1503 VRA
Power input	1200 watt
Power output	700 watt
Belt speed	4-12 m/sec
Belt dimensions	760 x 40/20 mm
Pipe Ø max.	125 mm
Weight	3,7 kg

Standard equipment	
1 sanding belt, continuous, P 80, 760 x 40 mm	1 piece of 326.739
1 sanding belt, continuous, P 120, 760 x 20 mm	1 piece of 326.801
1 sanding belt, continuous, P 220, 760 x 20 mm	1 piece of 326.836
1 sanding fleece, continuous, A 400, 760 x 40 mm	1 piece of 326.852
1 sanding fleece, continuous, A 240, 760 x 40 mm	1 piece of 326.879
1 sanding-polishing belt, continuous, S 600, 760 x 40 mm	326.917
1 sanding-polishing belt, continuous, S 1500, 760 x 40 mm	326.933
1 plastic carrying case with insert	327.603